



Colour Manager

- Powerful protection for sensitive data thanks to the innovative Toshiba Secure Hard Disk Drive
- Intelligent multifunctionality which meets all your needs
- Excellent colours to enhance your document quality
- User friendly MFP to ensure highest productivity
- Hassle free integration into your network

-STUDIO2040CSE
-STUDIO2540CSE
-STUDIO3040CSE
-STUDIO3540CSE
-STUDIO4540CSE



SAP® Printer Vendor Solution



e-STUDIO2040CSE
 e-STUDIO2540CSE
 e-STUDIO3040CSE
 e-STUDIO3540CSE





e-STUDIO2040CSE
e-STUDIO2540CSE **e-STUDIO3540CSE**
e-STUDIO3040CSE **e-STUDIO4540CSE**



General	Print & Copy Speed Warm-up Time Paper Size & Weight Paper Capacity Automatic Duplex Controller Type Memory Interface Dimensions & Weight	Colour: 20/25/30/35/45 ppm (A4), 10/15/16/18/22 ppm (A3) B&W: 20/25/30/35/45 ppm (A4), 10/15/16/18/22 ppm (A3) Approx. 30 seconds from low-power mode Cassettes: A5R-A3, 64-256 g/m ² Bypass: A6R-320 x 460 mm, 64-280 g/m ² , banner paper (305 x 1,200 mm, 90-163 g/m ²) ¹⁾ 2 x 550 sheets (Cassettes), 100 sheets (Bypass) Maximum: 3,700 sheets A5R-A3+, 64-256 g/m ² Toshiba e-BRIDGE Toshiba Secure HDD 160 GB ²⁾ , 1.5 GB RAM 10/100/1000 BaseT (incl. IPv6), High-Speed USB 2.0, WLAN ³⁾ (IEEE802.11b/g), Bluetooth ³⁾ 699 x 808 x 759 mm (W x D x H), ~ 121 kg
Print	Resolution Page Description Languages Supported Systems Colour Modes Colour Settings Print Functions	Max. 600 x 600 dpi, 8 bit per colour channel XPS, PCL6 and PostScript 3 compatible Windows 7/Vista/XP/Server 2008/Server 2003 (32/64 bit), Windows Server 2008 R2 (64 bit), Mac OS X, Linux/UNIX, Novell Netware (NDPS), Citrix, SAP, AS/400 Auto-Colour (ACS), Colour, Twin Colour, B&W Brightness, Saturation, Contrast, Colour Balance, ICC profiles management Universal Driver, Driver templates, Driver plug-ins, Private/Hold print, Print from USB, Tandem Printing, etc.
Scan	Resolution Scan Speed Scan Modes File Formats Scan Functions	Max. 600 x 600 dpi, 8 bit per colour channel Colour & B&W: Up to 57 ipm (300 dpi) Auto-Colour (ACS), Colour, Greyscale, B&W JPEG, Multi/Single Page TIFF/XPS/PDF, Secure PDF, Slim PDF, Searchable PDF ³⁾ (and other editable formats like DOC, XLS, RTF, TXT, PDF/A) ³⁾ WS Scan (pull/push), Scan to USB, Scan to E-Mail, Scan to File (SMB, FTP, FTPS, IPX/SPX, local), Meta Scan ³⁾ , Scan to Box (e-Filing), TWAIN 1.7/1.8/1.9
Copy	Resolution First Copy Output Time Zoom Copy Modes Colour Modes Colour Settings	Scan: 600 x 600 dpi, 10 bit per colour channel Print: 600 x 600 dpi, 8 bit per colour channel 2,400 x 600 dpi, B&W with smoothing Colour: Approx. 8.4/8.4/8.4/8.4/6.8 seconds B&W: Approx. 6.5/6.5/6.5/6.5/5.2 seconds 25-400% (platen), 25-200% (RADF) ³⁾ Text, Text/Photo, Photo, Printed Image, Map Auto-Colour (ACS), Full Colour, Twin Colour, Mono Colour, B&W Hue, Saturation, Colour Balance, 5 One-touch Modes, RGB Adjustment
Fax³⁾	Communication Transmission Speed Compression Network-Fax Incoming Fax Routing	Super G3, G3 - (opt. 2 nd line), Internet Fax T.37 Approx. 3 seconds per page JBIG, MMR, MR, MH Driver for Windows 7/Vista/XP (32/64 bit), etc. To shared folders (SMB, FTP, IPX/SPX), E-mail, e-Filing
System & Security	Device Management System Features Accounting & Security	e-BRIDGE Fleet Management System ³⁾ , TopAccess for remote administration and configuration e-Filing document server for secure storage, document distribution and Print on Demand (1 public box, 200 user boxes), 12,060 One-touch Templates for storage of personalised settings or workflows, Scan/Fax preview, RIP-while-Print, e-BRIDGE Open Platform ³⁾ , Embedded Web Browser, Job Skip Role Based Access, LDAP support, 1,000 department codes & 10,000 user codes, card reader ³⁾ , Quota management, standard data encryption with Toshiba Secure HDD, Data Overwrite Enabler ³⁾ , IP and MAC address filter, port filter, support of SSL and IPsec ³⁾ protocols, IEEE802.1x support, IEEE2600.1 compliant ³⁾ , Scan to secure PDF, Hard Copy Security Kit ^{3/4)} Productivity and paper specifications are related to a paper size of A4 and a paper weight of 80 g/m ² if not otherwise mentioned.

OPTIONS

RADF – MR-3021 / MR-3022

100-sheet capacity, A5R-A3, 35-157 g/m²

HANGING FINISHER – MJ-1031

1 tray, 1,000-sheet capacity
 50-sheet single position stapling
 A5R-A3, 64-105 g/m² (stapling mode)
 411 x 595 x 383 mm (W x D x H), ~ 12 kg

MULTI-STAPLING FINISHER – MJ-1101

2 trays, 2,250-sheet capacity
 50-sheet multi-position stapling
 A5R-A3, 64-105 g/m² (stapling mode)
 535 x 598 x 1,092 mm (W x D x H), ~ 34 kg

SADDLE-STITCH FINISHER – MJ-1106

2 trays, 3,250-sheet capacity
 50-sheet multi-position stapling
 5-sheet center-folding
 Saddle-stitched booklets of up to 60 pages
 A5R-A3, 64-105 g/m² (stapling mode)
 617 x 603 x 1,085 mm (W x D x H), ~ 70 kg

HOLE PUNCH UNIT – MJ-6103

Option for Finisher MJ-1101/MJ-1106
 Available in 2 holes (E), 4 holes (F), 4 holes (S)
 112 x 573 x 323 mm (W x D x H), ~ 7 kg

PAPER FEED PEDESTAL – KD-1027

550 sheets (1 cassette), A5R-A3, 64-256 g/m²
 623 x 643 x 320 mm (W x D x H), ~ 21 kg

LARGE CAPACITY FEEDER – KD-1028A4

2,500-sheet capacity, A4, 64-105 g/m²
 623 x 643 x 308 mm (W x D x H), ~ 27 kg

OTHER OPTIONS

DESK – MH-1710
 CASSETTE – MY-1035
 FAX BOARD – GD-1250EU
 DATA OVERWRITE ENABLER – GP-1070
 e-BRIDGE ID-GATE – KP-2004/5, TWN3XX
 WIRELESS LAN MODULE – GN-1060
 BLUETOOTH MODULE – GN-2010
 META SCAN ENABLER – GS-1010
 HARD COPY SECURITY KIT – GP-1190⁴⁾
 IPsec ENABLER – GP-1080
 e-BRIDGE Re-Rite – GB-1280
 DAMP HEATER KIT – MF-3500CE

¹⁾ With Toshiba waterproof banner paper up to 230 g/m²
²⁾ 1 GB = 1 billion bytes; the actual formatted capacity is less. Available capacity will also be less if software applications are pre-installed.
³⁾ Optional
⁴⁾ Not available at time of print